



Installation Instructions

ShadeMaker™ Mesh Bimini, Bimini Plus Tops for 2018-Current Jeep® JL/JLU Wrangler Vehicles Items #142016XX, #142026XX, #142015XX, #142025XX

ShadeMaker Bimini Top Plus for 4 Door shown for illustration.



Bimini Top Parts List:
Mesh Front Section - QTY 1

Bimini Top Plus Parts List:
Mesh Front Section - QTY 1
Mesh Rear Section - QTY 1

Required Tools:
Safety Glasses
T25 Torx Bit & Driver (Bimini Plus Only)



Freedom Mesh Shown Installed under Freedom Panel

⚠ WARNING ⚠

Loss of vehicle control involves risk of death or serious injury, particularly to parts of your body not restrained within vehicle. This product is intended for weather protection only and should not be relied upon to contain occupants in the event of an accident or to protect from either ground contact or falling objects. To reduce risk of accident or injury:

- ALWAYS WEAR SEATBELTS
- Always keep head, arms & body parts within vehicle.
- Fully secure or stow the soft top before driving according to instructions. Never try to latch or fold soft top while driving. Do not use if damaged or worn.
- Read and follow all instructions & warnings accompanying this product, in your vehicle owner's manual and Off Road Driving Supplement.

⚠ CAUTION ⚠

RISK OF EYE INJURY. Safety glasses should be worn at all times while installing or maintaining this product.



Important Safety information

Your MasterTop® ShadeMaker™ Bimini Top and Bimini Top Plus is intended to increase the fair weather enjoyment of your off-road capable vehicle. Before installation, please take a moment to review the following safety information and installation instructions. Important safety information is generally preceded by one of three signal words indicating the relative risk of injury. The signal words mean:

⚠ WARNING ⚠	A hazardous situation which, if not avoided, could result in death or serious injury. You CAN be KILLED or SERIOUSLY HURT if you don't follow instructions.
⚠ CAUTION ⚠	A hazardous situation which, if not avoided, could result in minor or moderate injury. You CAN be moderately HURT and also may suffer property damage if you don't follow instructions.
NOTICE	Careful attention is required to this instruction or operation but does generally not relate to personal injury. Damage to your MasterTop product or other property may result if you don't follow instructions.

Before you begin Installation:

We are excited that you have chosen the MasterTop ShadeMaker Mesh Bimini Top/Bimini Top Plus! These high quality tops are designed to enhance your fair weather driving pleasure while providing needed shade while driving in the hot sun. Please note that it is important that you become familiar with the installation process of this top by reading the following instruction sheet and warnings thoroughly. Though we use only the finest materials in creating this top, any product that is exposed to the elements requires some general maintenance to keep it looking like new. Please see page 6 for these important maintenance tips. Please also note that it is normal for the mesh fabric to contract and wrinkle when stored in the shipping carton. In a few days the fabric will relax and wrinkles will disappear.

When unpacking, check to make sure all parts are included.

If any part is missing or broken, please call MasterTop customer service at 720-575-5440.

IMPORTANT Instruction Sheet Strap Installation Note: (all versions)

Installing the MasterTop ShadeMaker Mesh tops entails the wrapping of nylon webbing around several locations on your factory installed sport bar. In order to simplify the installation process, the following instructions show the general location of these straps and may not match exactly to the model you purchased. In all cases, the straps are to be wrapped around the sport bar and not around the door surround hardware unless noted.



Threading Straps through Buckles:

Throughout the installation, you will need to thread webbing straps through buckles several times. Please review the picture for correct strap routing through the buckles. As a rule of thumb, run the strap below and through the sewn side of the buckle first and then back down through the end of the buckle. Tighten the strap by simply pulling the exposed webbing after threading the strap through the buckle.

NOTICE	Remove your factory hard or soft top before installation. For those vehicles with a factory soft top, you will NOT be using your factory soft top header for this installation.
---------------	---

The ShadeMaker Mesh Top Concept:

The MasterTop ShadeMaker Mesh Bimini Top/Bimini Top Plus series are designed as an easy-on, easy off sun shade for your Jeep. The tight mesh weave is specially designed to block the heat caused by the sun while letting light and air to flow freely. The installation of these products is easy and requires no tools or windshield header, and allows this product to be left on while you run your hard or your soft top.

Enjoy the shade and thank you for purchasing MasterTop products!



Installation of ShadeMaker Bimini and Bimini Plus Top:



Step 1: Attach The Mesh Front Section to the Front Windshield Pillar


Put on safety glasses.

After removing your hard top or soft top, locate the front section of your Bimini top Plus and drape the Front mesh fabric over the top of your Jeep with the flat straight edge facing forward.



Wrap the long front straps around the Sport Bar, through the gap between the front roll bar and the windshield and back to the buckle on the strap. See FIGS 1 & 2. Repeat on the other side of the vehicle.

Tighten each side strap making sure the top is centered on the vehicle. See FIG 3.



Step 2: Attach Front Section to Rear B Pillar

Locate the two rear corner straps and wrap around the "B" pillar. Thread the straps through the buckle and secure making sure the top is centered on the vehicle. See FIGS 4 & 5. Repeat on the other side of the vehicle.



Once the rear corner straps are secure and the top is centered, locate the two rear center straps with the hooks on the ends of the straps (See FIG 6).

Thread the drivers side hook strap through the buckle and hook the strap into the hole located in front of the sound bar as shown in FIG 6.


Repeat this on the other side. Secure all straps while making sure the top is centered. If centered properly, the top will have very few if any wrinkles in it.

Front Mesh Bimini Top Installation is now complete.

See following pages for installation of Rear Section.



Installation of ShadeMaker Bimini Plus Top:



Step 3: Attaching the Rear Mesh to B Pillar


On the Rear Mesh, locate the two center buckle straps with the hook straps. FIG7.

Thread the hook straps into the center buckles and hook the straps into the holes located in FIG 8. Do not tighten yet.

On the rear mesh section, locate the two front corner straps (See FIG7). Thread the front facing buckle with the hook strap and insert the hook into the hole shown in FIG9. Do not tighten yet.



Take the side facing strap, wrap around the side roll bar and thread it through the attached buckle (FIG10). Again, do not tighten yet.



Step 4A: Attaching the Rear Mesh to Back of the Roll Bar Assembly

Locate the rear two straps on the rear mesh (FIG11). Wrap the side facing strap around the rear of the roll bar locating it in the "notch" shown in FIG12. Take the rear facing strap and secure it to the side strap under the roll bar. Thread the strap through the buckle and secure. At this point you will need to tighten all straps previously installed in steps 3 and 4 making sure the rear top is centered on the vehicle. Start from the front center straps and work out and back to the rear pulling out any wrinkles.



Installation of ShadeMaker Bimini Plus Top:



Step 4B: Attaching the Rear Mesh to Rear of the Roll Bar Assembly

This step will require the use of a T25 Torx bit and driver. You will be removing two Torx screws from the rear roll bar and re-installing them back into the same holes. Locate the two center cutouts on the rear of the Roll bar. (FIG14). With a T25 Torx, remove the two Screws located in these cutouts and place them through the two rear strap holes attached to the top (FIGS 15 &16).

With the rear straps threaded through the rear buckles, tighten these straps. FIG17

Rear Mesh Bimini Top Installation is now complete. See next page regarding excess strap length.



NOTICE

After installing the two rear straps in step 4, you may have to adjust the other straps to take out any wrinkles. The two rear straps mounted to the center of the rear roll bar are designed to keep the rear portion from excess flapping while driving and to make sure your top remains tight.



After Installation Strap Maintenance



FIG18

Shorten Excess Length from Straps

To ensure installation of the Freedom Mesh Top goes as smoothly as possible, we have made several of the straps longer in length than is necessary.

To shorten the straps follow the following procedure: With the top completely installed, using heavy duty scissors cut the desired length of strap at a 45 degree angle (Angle makes threading strap through buckle easier for future installs) (Fig18). Using a lighter, carefully singe the ends of the strap (run the flame quickly back and forth over the end of the strap) being careful not to catch the strap on fire and keeping your fingers a safe distance from the fire (Figs19 & 20). This singeing process will seal the ends of the strap and keep it from unraveling. Repeat this procedure on any strap you deem to be too long. See Warning below!



FIG19



FIG20

⚠ WARNING ⚠

Potential Fire and Burn hazard. When singeing the ends of the straps never let it catch on fire. Always have a fire extinguisher handy in case the strap does catch on fire. Once the Strap is singed, DO NOT touch the end of the strap as to avoid the potential for burning skin. Always singe the straps outside in a well ventilated area away from any fuel or the vehicle itself.

Care and Maintenance of your MasterTop ShadeMaker™ Bimini, Bimini Plus and Cargo Tops:

Your MasterTop ShadeMaker Bimini Top or Bimini Top Plus is made of the finest materials available but to keep it looking new and for the maximum possible wear, it will need periodic cleaning and basic maintenance. The main threat to your soft top is pollutants, dirt and grime. By keeping your top clean you will prolong the life of your top.

We recommend the following to keep your top like new:

Washing:

The top fabric should be washed often using a mild soap, warm water and a soft bristle brush. You can also use special soft top cleaners available on our Distributors websites. Make sure that after cleaning you rinse with clear water to remove all traces of soap to avoid residue. Hang to dry, do not put a ShadeMaker Top in a clothes dryer.

For more information on MasterTop:

This and other helpful product information is available on www.mastertop.com
Please visit our website frequently for product updates and exciting news.





The Ultimate Add-On Accessory for your NEW Mesh Top: Introducing the NEW MasterTop JL Cab Cover!



Keeps the heat out!



Protects Door Openings



Easy on, Easy Off!

MasterTop JL Cab Cover:

- ✓ Quick & Easy Protection from the elements
- ✓ Durable cover protects while the full top is off
- ✓ Perfect companion for your Shademaker Mesh Bimini Top or Bimini Top Plus
- ✓ Protects from water, dust, dirt and those harmful UV Rays
- ✓ Waterproof fabric with seams specifically designed to prevent pooling
- ✓ Long side panels fully protect door opening as well

Contact your MasterTop distributor TODAY for this great new cover!





Limited 3 Year Warranty

Your MasterTop® accessory is covered by the following Limited Warranty provided exclusively by MasterTop, Inc., 420 J Corporate Circle, Golden, CO 80401.

This Limited Warranty is the only warranty made in connection with your purchase. MasterTop neither assumes nor authorizes any vendor, retailer or other person or entity to assume for it any other obligation or liability in connection with this product or Limited Warranty. This Limited Warranty does not apply and is not cumulative to any accessory or part distributed by any MasterTop distributor for which the Manufacturer provides a separate written warranty.

What is Covered: Subject to the terms, exclusions and limitations herein and with respect only to MasterTop branded accessories first sold in the United States, MasterTop warrants to the initial retail purchaser only that your MasterTop accessory shall be free of defects in material and workmanship; **for a period of 3 years from date of initial retail sale.**

All other warranties are hereby disclaimed, except to the extent prohibited by applicable law in which case any implied warranty of merchantability or fitness for a particular purpose on this product is **limited to 3 years from date of initial retail sale.** MasterTop reserves the rights to: (a.) require invoice or other proof your product is within the terms of this Limited Warranty as a condition of warranty service and, (b.) make future revisions to this product and Limited Warranty without prior notice or obligation to upgrade your product.

What is Not Covered: Your MasterTop Limited Warranty does not cover products or parts MasterTop determines to have been damaged by or subjected to: (a.) installation damage, alteration, modification, failure to maintain or attempted repair or service by anyone not authorized by MasterTop, (b.) normal wear and tear, cosmetic damage or damage from water immersion, (c.) Acts of God, accidents, misuse, negligence, inadequate mounting or impact with vehicle(s), obstacles or other aspects of the environment, (d.) theft, vandalism or other intentional damage, (e.) fleet, rental or commercial use, (f.) use in competition or racing.

Remedy Limited to Repair/Replacement: The exclusive remedy provided hereunder shall, upon MasterTop inspection and at MasterTop's option, be either repair or replacement of product or parts (new or refurbished) covered under this Limited Warranty. Customers requesting warranty consideration on MasterTop Products should first contact MasterTop to obtain a RGA number (720-575-5440). All labor, removal, shipping and installation costs are customer's responsibility.

Other Limitations - Exclusion of Damages - Your Rights Under State Law:

In consideration of the purchase price paid, neither MasterTop nor any independent MasterTop distributor /licensee are responsible for any time loss, rental costs, or for any incidental, consequential, punitive or other damages you may have or incur in connection with any part or product purchased. Your exclusive remedy hereunder for covered parts is repair/replacement as described above.

This Limited Warranty gives you specific rights. You may also have other rights that vary from state to state. For example, some states do not allow limitations of how long an implied warranty lasts and/or do not allow the exclusion or limitation of incidental or consequential damages, so the limitations and exclusions herein may not apply to you.

©MasterTop, Inc. 2018. All Rights Reserved. The term MasterTop® is a Registered Trademark of MasterTop Incorporated, Registered in U.S. Patent and Trademark Office.

www.MasterTop.com

Part #941026.01 Version 8.28.18 LTR

