



Protecting Your Adventure Lifestyle

Warrior Products, Inc.  
16850 SW Upper Boones Ferry Rd  
Ste. A  
Durham, OR 97224  
Phone (888) 220-6861  
Fax (503) 692-0364  
customerservice@warriorproducts.com

---

---

## **MAXI-BREEZER TOP**

### **INSTALLATION INSTRUCTIONS**

### **WAR 1145**

### **TJ '03-'06**

NOTE: Installation of this top requires a windshield retaining channel, if you do not have one it can be purchased at your local offroad shop- Bestop part #51238-01

TOOLS NEEDED: #30 Torx Driver

1. Use #30 Torx Driver to remove 2 Torx screws in each speaker pod – let them hang in place
2. Install windshield retaining channel if needed
3. Turn Maxi-Breezer Top upside down & install to channel, make sure space between top fabric and windshield flange is the same on both sides
4. Flip Maxi-Breezer Top over (keeping pressure on top while flipping to keep it from coming loose from channel)
5. Wrap long center strap around sport bar & fasten through footman loop on windshield frame then tighten securely
6. Attach corner straps and cinch until you have proper tension
7. Attach & cinch remaining straps until you have a tight fit
8. Reattach speaker pods
9. Extend remaining portion of Maxi-Breezer Top over rear Roll Cage and secure rear straps around shoulder strap mount on Roll Bar on each side until you have proper tension
10. Adjust 4 side straps (2 on each side) until you have a tight fit

Your Maxi-Breezer Top is now fully installed. **Enjoy!**

If you need further assistance installing your product, please contact us by email at [customerservice@warriorproducts.com](mailto:customerservice@warriorproducts.com) or call us at (888) 220-6861.

## **THANK YOU FOR PURCHASING WARRIOR PRODUCTS**